



**Vee Rubber**

**PERFORMANCE TIRES**



**EXTRA LOAD TIRE**

SFS-PLUS  
LUG



VT107

SFS-PLUS  
RIB



VT108

SFS-119



VT119

LUG



VT101 VT122

RIB



VT102C VT103C VT104C

RIB



VT113 VT114 VT115 VT116 VT121

EXTRA LOAD TIRE

 **Vee Rubber**

## COMB



VT106 VT112

## LIGHT TRUCK



VT141 VT173

## SAFARI



VT111



VT215

## SNOW



VT105

## MUD + SNOW



VT110

# EXTRA LOAD TIRE

 **Vee Rubber**

# VT 101 LUG



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.00-13	8	4.5	175	658	675	640	60	60
6.00-14	6	4.5	172	683	610	580	46	46
	8	4.5	172	683	710	675	60	60
6.50-14	10	4.5	172	683	810	760	75	75
	8	4.5	183	699	795	755	60	60
7.00-15	12	5.5	201	756	1150	1093	84	84
	14	5.5	201	756	1270	1207	99	99
7.00-16	12	5.5	205	800	1170	1115	82	82
	14	5.5	205	800	1265	1200	93	93
7.50-15	12	6	228	790	1315	1250	85	85
	14	6	228	790	1415	1345	99	99
7.50-16	10	6	208	811	1265	1200	75	75
	12	6	208	811	1370	1305	85	85
	14	6	208	811	1475	1405	96	96
8.25-16	14	6.5	241	982	1630	1550	85	85
	16	6.5	241	982	1760	1670	95	95
8.25-20	14	6.5	241	982	2180	1950	96	96
9.00-20	14	7	255	1025	2300	2185	96	96
10.00-20	16	7.5	274	1060	2760	2485	105	105
11.00-20	16	8	290	1092	2900	2610	105	105
12.00-20	18	8.5	320	1130	3170	3015	114	114
12.00-24	18	8.5	309	1231	4000	3650	112	112

## EXTRA LOAD **SUPER 5 STARS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	183	699	910	865	75	75
7.50-16	16	6	208	811	1580	1500	107	107
9.00-20	16	7	255	1025	2455	2330	107	107
10.00-20	18	7.5	274	1060	3095	2790	114	114
11.00-20	18	8	290	1092	3130	2975	114	114



# VT 102 RIB

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.00-13	8	4.5	169	637	675	640	60	60
6.00-14	6	4.5	173	684	610	580	46	46
	8	4.5	173	684	710	675	60	60
6.50-14	8	4.5	183	699	795	755	60	60
6.50-16	8	4.5	180	761	870	825	60	60
	10	4.5	180	761	960	915	70	70
	12	4.5	180	761	1050	995	82	82
7.00-15	10	5.5	204	774	1030	980	71	71
	12	5.5	204	774	1150	1095	85	85
7.00-16	10	5.5	204	790	1075	1020	71	71
	12	5.5	204	790	1170	1115	82	82
	14	5.5	204	790	1265	1200	93	93
7.50-15	12	6	220	784	1315	1250	85	85
	14	6	220	784	1415	1345	99	99
7.50-16	10	6	220	811	1265	1200	75	75
	12	6	220	811	1370	1305	85	85
	14	6	220	811	1475	1405	96	96
8.25-20	14	6.5	238	986	2180	1950	96	96
	16	6.5	238	986	2033	1931	103	103

## EXTRA LOAD



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	183	699	910	865	75	75

# VT 103C

## RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	16	8	302	1095	2900	2610	105	105

### EXTRA LOAD **SUPER 5 STARS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	18	8	302	1095	3130	2975	114	114



# VT 104C

## TRAILER

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
10.00-20	16	7.5	275	1057	2760	2485	105	105

# VT 105

## MUD & SNOW



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	8	4.5	188	719	795	755	60	60

### EXTRA LOAD

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	188	719	910	865	75	75

# VT 106

## COMB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.50-16	10	6	202	792	1265	1200	75	75
	12	6	202	792	1370	1305	85	85
	14	6	202	792	1475	1405	96	96

# VT 107

## SFS-PLUS



**EXTRA LOAD** **SUPER 5 STARS** **PLUS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.50-16	16	6	224	836	1580	1500	107	107
9.00-20	16	7	262	1026	2455	2332	107	107
10.00-20	16	7.5	280	1083	2760	2485	105	105
	18	7.5	280	1083	3095	2790	114	114
11.00-20	16	8	300	1113	2900	2610	105	105
	18	8	300	1113	3095	2790	114	114
	20	8	300	1113	3130	2975	114	114
12.00-20	20	8.5	344	1157	3375	3206	135	135

# VT 108

## SFS-PLUS



**EXTRA LOAD** **SUPER 5 STARS** **PLUS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	16	7	265	1028	2455	2330	107	107
10.00-20	18	7.5	288	1053	3095	2790	114	114
11.00-20	18	8	305	1112	3130	2975	114	114



# VT 112 COMB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
8.25-20	14	6.5	233	987	2180	1950	96	96
	16	6.5	233	987	2033	1931	103	103

# VT 113 RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	14	7	258	1024	2300	2185	96	96
10.00-20	16	7.5	277	1060	2760	2485	105	105

## EXTRA LOAD **SUPER 5 STARS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	16	7	258	1024	2455	2330	107	107
10.00-20	18	7.5	277	1060	3095	2790	114	114

# VT 114

## RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
12.00-20	18	8.5	317	1125	3170	3015	114	114

# VT 115

## RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	16	8	297	1097	2900	2610	105	105

### EXTRA LOAD **SUPER 5 STARS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	18	8	297	1097	3130	2975	114	114

# VT 116

## RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
8.25-16	14	6.5	225	847	1630	1550	85	85
	16	6.5	225	847	1760	1670	95	95

# VT 119



**EXTRA LOAD** **SUPER 5 STARS** **PLUS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	16	7	262	1045	2455	2330	107	107

# VT 121

## RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
10.00-20	16	7.5	276	1055	2760	2485	105	105

# VT 122

## LUG



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
10.00-20	16	7.5	277	1058	2760	2485	105	105



# VT 110 M+S MUD & SNOW

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.50-16	14	6	232	837	1475	1405	96	96



# VT 111 SAFARI

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	8	4.5	189	703	795	755	60	60

## EXTRA LOAD **SUPER 5 STARS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	189	703	910	865	75	75

# VT 127

## SEMI-LUG



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.00-15	8	5.5	205	763	935	888	60	60
12.00-24	18	8.5	321	1251	4000	3650	112	112

# VT 141

## SMALL LIGHT TRUCK



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
5.00-10	8	3.5	144	514	295	280	51	51
5.00-12	8	3.5	148	566	485	460	56	56

# VT 173

## SMALL LIGHT TRUCK



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
5.00-12	8	3.5	137	558	485	460	56	56

# VT 215

## LIGHT TRUCK



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
5.00-12	10	3.5	144	569	555	525	71	71
6.50-14	8	4.5	190	711	795	755	60	60

### EXTRA LOAD

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	190	711	910	865	75	75



## Contact Us

**Vee Tyre and Rubber Co., LTD.**

Address : 924 Rama 9 Road,  
Bangkapi, Huay-Kwang,  
Bangkok 10310, Thailand.

Tel : (662)719-6644-5  
Fax : (662)719-6661-2  
E-mail : [info@veerubber.co.th](mailto:info@veerubber.co.th)  
Website: [www.veerubber.co.th](http://www.veerubber.co.th)

